

## QMP 6000 Series

Not our father's ECR. The definitive cash register for the age of the Cloud.



Meets all fiscal requirements



Cloud back-office capability (QBC)



Different printer and keyboard options

## **Highlights:**

- Adjustable operator display
- Increased security with LINUX operating system
- Supports LAN networks
- Reliable & fast thermal printer
  - USB host interfaces
- Integrated dallas lock



## **Stylish Design Meets Today's Performance Standards**

The QMP 6000 combines the familiar QUORION POS functions with a distinctive design. The QMP 6000 conveys precision, clarity, and dynamics. Exactly what today's merchant expects.

The embedded LINUX operating system allows

the cash register to operate on equal footing with current mPOS and PC POS systems. There is no other cash register that can deliver the same POS, networking, and cloud based capabilities.

## QMP 6000 Series





With its adjustable operator display, built-in customer display, and magnetic user lock, the QMP 6000 can serve many different business types. Resellers will reach more merchants and serve larger chains.

The QMP 6000 series offers 2 keyboard options plus 3 printer versions.





Raised keyboard (112 keys)

Flat keyboard (128 keys)

| Technical Specifications |   |                 |                             |
|--------------------------|---|-----------------|-----------------------------|
| QMP 6000 Series          |   |                 |                             |
| CPU                      | ARM Cortex-A9 400 MHz   | Keyboard        | 112 keys, raised            |
| Operating System         | LINUX with QMP software   |                 | 128 keys, flat              |
| Working Memory           | 32 MB SDRAM   | Interfaces      | Serial: 2 x RS232-5V (RJ45) |
| System Memory            | 4 GB eMMC   |                 | USB type A: 3 x USB 2.0     |
| Memory Expansion         | via USB   |                 | USB type B: 1 x USB 2.0     |
| Operator Display         | LCD multiline, 192 x 64 px, blue<br>backlight, graphics capable |                 | LAN: 1 x 100 MBit           |
|                          |   |                 | Cash drawer: 1 x RJ11-24V   |
| Customer Display         | LCD multiline, 192 x 32 px, blue<br>backlight, graphics capable | Power Supply    | 24.0 V DC, 2.5 A (external) |
|                          |   | Weight          | 2.0 kg                      |
| Receipt Printer          | 58 mm without cutter  | Dimensions      | 365 x 105 x 335 mm (LxHxB)  |
|                          | 58 mm with cutter   | Operating Temp. | 0°C - + 40°C                |
|                          | 80 mm with cutter   | Storage Temp.   | -20°C - + 60°C              |

